



Descrizione

Intrecciata diagonalmente e realizzata con filato aramidico a fibra discontinua di alta qualità, impregnata con PTFE e con lubrificante esente silicone.

Treccia molto compatta per applicazioni con alte pressioni e velocità, ottima per la sostituzione delle trecce in amianto impregnate con PTFE, è particolarmente adatta per l'utilizzo con fluidi abrasivi.

Applicazioni

Questa mescola viene utilizzata principalmente per valvole ad alte velocità, tenute statiche e moti alternativi a contatto con liquidi abrasivi, acqua, prodotti chimici e caustici leggeri.

Parametri	U. di misura	Valore
Temperatura max	°C	-100 +280
Pressione	bar	20 - 150
PH	-	2 - 12
V	m/s	15
Densità	g/cm3	1,7





Product Description:

Braid consisting of discontinuous Kevlar yarn treated strand by strand with pure graphite powder, inert lubricant, corrosion inhibitor, and manufactured using a diagonal braiding system.

Application:

This compound is mainly used for high-speed valves, static seals and reciprocating motions in contact with abrasive liquids, water, chemicals and light caustics.

Notice:

The operating temperature and pressure limits do not apply simultaneously; they depend

Parameters	U. of measure	Value
Max temperature	°C	-100 +280
Pressure	bar	20 - 150
PH	-	2 - 12
V	m/s	15
Density	g/cm3	1,7

